MIL-SPEC ATACRTM 1-8x24mm F1 S-VPS KIT

LIMITED PRODUCTION RUN

The MIL-SPEC line of scopes are adapted versions of the proven ATACR[™] family. Nightforce MIL-SPEC riflescopes undergo additional testing to ensure that they will perform reliably, repeatedly, and without fail, when combat conditions are at their worst.

This is a limited production run of 300 units of the United States Special Operations Command (USSOCOM) Squad Variable Power Scope (S-VPS) which is part of the Miniature Aiming Systems-Day Optic (MAS-D) program. This includes a MIL-SPEC ATACR[™] 1-8x24mm F1 with Horus TREMOR8[™] Reticle and includes the accompanying accessories, mounting kit, tools, and manuals all in the commemorative hard case.



NIGHTFØRCE

Nightforce Optics, Inc. | 336 Hazen Lane | Orofino, ID 83544 | 208.476.9814 | info@nightforceoptics.com | www.nightforceoptics.com Nightforce Optics, Inc. 2023 All information herein's accurate at time of printing. Specifications and product appearances subject to change without notice, REV 1123 The appearance of Defense DDD Visati Information due not informat

KIT CONTENTS	1/17	20	NIT	E 1 1 7	F.C.
	KII	しし	NI	ENI	3

SU-294 PVS FFP ATACR 1-8x24	1240-01-681-3209
FLIP-UP LENS CAP, EYEPIECE (TAN)	6650-20-012-1291
FLIP-UP LENS CAP, OBJECTIVE (TAN)	6650-20-012-1292
BATTERY, CR2032	6135-01-210-8715
ULTRAMOUNT 34mm (COMPLETE)	1240-01-681-3233
MAGPUL PRO OFFSET SIGHT - FRONT	1240-01-681-3316
MAGPUL PRO OFFSET SIGHT - REAR	1240-01-681-3311
OPTICAL CLEANING KIT	1240-01-654-6164
TORQUE TOOL FIELD KIT 100-IN/LB	5120-01-681-3318
PADDED SCOPE CASE (COYOTE)	8105-01-681-3308
OPERATOR'S MANUAL	SOFWEA-18-G10-00031-00
FIELD GUIDE	SOFWEA-18-G10-00032-00

SPECIFICATIONS			
MAGNIFICATION RANGE	1-8×		
FOCAL PLANE	First		
WEIGHT	24 oz 680 g		
OVERALL LENGTH	10.1 in 255.5 mm		
BODY TUBE DIAMETER	34 mm		
MOUNTING LENGTH	5.67 in 144 mm		
EXIT PUPIL DIAMETER	1x: 11.26 mm 8x: 3.19 mm		
FIELD OF VIEW @ 100 M/YD	@100m: 1x: 32.0 m 8x: 4.4 m @100y: 1x: 96.1 ft 8x: 13.1 ft		
EYE RELIEF	3.74 in 95 mm		

 PARALLAX ADJUSTMENT
 Fixed at 125 m

 INTERNAL ADJUSTMENT RANGE
 E: 30 Mil-Radian I W: 30 Mil-Radian

 ADJUSTMENT VALUE
 1 Mil-Radian per click

ELEVATION FEATURE Capped, finger-adjustable

POWER THROW LEVER Standard

RETICLE Horus TREMOR8™